

Single Bearing Vibration Limits (Velocity)

Bore Diameter (mm)	Diameter Series 0				Diameter Series 2					Diameter Series 3				
	Z	Z1	Z2	Z3	Z	Z1	Z2	Z3	Z4	Z	Z1	Z2	Z3	Z4
3	35	34	32	28	36	35	32	30	-	37	36	33	31	-
4	35	34	32	28	36	35	32	30	-	37	36	33	31	-
5	37	36	34	30	38	37	34	32	-	39	37	35	33	-
6	37	36	34	30	38	37	34	32	-	39	37	35	33	-
7	39	38	35	31	40	38	36	34	-	-	-	-	-	-
8	39	38	35	31	40	38	36	34	-	-	-	-	-	-
9	41	40	36	32	42	40	37	35	-	-	-	-	-	-
10	43	42	38	33	44	42	39	35	30	37	44	40	37	32
12	44	43	39	34	45	43	39	35	30	47	45	40	37	32
15	45	44	40	35	46	44	41	36	31	48	46	42	38	33
17	46	44	40	35	47	45	41	36	31	49	47	42	38	33
20	47	45	41	36	48	46	42	38	33	50	48	43	39	34
22	47	45	41	36	48	46	42	38	33	50	48	43	39	34
25	48	46	42	38	49	47	43	40	36	51	49	44	41	37
28	49	47	43	39	50	48	44	41	37	52	50	45	42	38
30	49	47	43	39	50	48	44	41	37	52	50	45	42	38
32	50	48	44	40	51	49	45	42	38	53	51	46	43	39
35	51	49	45	41	52	50	46	43	39	54	52	47	44	40
40	53	51	46	42	54	52	47	44	40	56	54	49	45	41
45	55	53	48	45	56	54	49	46	43	58	56	51	47	44
50	57	54	50	47	58	55	51	48	45	60	57	53	49	46
55	59	56	52	49	60	57	53	50	47	62	59	54	51	48
60	61	58	54	51	62	59	54	51	48	64	61	56	53	50

Single Bearing Maximum Vibration Acceleration

Bore Diameter (mm)	V			V1			V2			V3			V4		
	Low Freq.	Medium Freq.	High Freq.	Low Freq.	Medium Freq.	High Freq.	Low Freq.	Medium Freq.	High Freq.	Low Freq.	Medium Freq.	High Freq.	Low Freq.	Medium Freq.	High Freq.
3,4	80	44	44	60	35	32	48	26	22	31	16	15	28	10	10
5,6	110	72	60	74	48	40	58	36	35	35	21	18	32	11	11
7,8,9	130	96	80	92	66	54	72	48	44	44	28	24	38	12	12
10,12	160	120	100	120	80	70	90	60	55	55	35	30	45	14	15
15	210	150	120	150	100	85	110	78	65	65	46	35	52	18	18
17	210	150	120	150	100	85	110	78	65	65	46	35	52	25	25
20	260	190	150	180	125	100	130	100	80	80	60	45	60	25	25
22,25	260	190	150	180	125	100	130	100	80	80	60	45	60	30	32
28	260	190	150	180	125	100	130	100	80	80	60	45	60	35	40
30,32	300	240	190	200	150	130	150	120	90	90	60	60	70	35	40
35	300	240	190	200	150	130	150	120	90	90	75	60	70	42	45
40	360	300	260	240	180	160	180	150	110	110	90	80	82	50	50
45	360	300	260	240	180	160	180	150	110	110	90	80	82	60	60
50	420	320	320	280	200	200	210	160	160	125	100	100	95	70	70